

# Gasket Constants

Product Style	Thickness	Gb	a	Gs	S100	S1000	S3000	S5000	S10000	Tpmin	Tpmax
3500	1/16"	949	0.253	2.60E+00	3,043	5,448	7,194	8,187	9,756	373	16,890
3500	1/8"	1980	0.169	3.93E-01	4,313	6,365	7,663	8,354	9,393	223	25,375
3504	1/16"	183	0.357	4.01E-03	947	2,155	3,190	3,828	4,903	3,097	14,817
3504	1/8"	1008	0.221	2.23E+00	2,793	4,649	5,928	6,638	7,739	141	72,992
3510	1/16"	289	0.274	6.61E-11	1,021	1,918	2,592	2,981	3,605	11,881	25,501
3510	1/8"	444	0.332	1.29E-02	2,048	4,399	6,336	7,507	9,449	1,770	17,550
3535	3/8"	430	0.286	1.69E-09	1,605	3,101	4,245	4,913	5,991	373	
3540	1/16"	550	0.304	7.64E-01	2,230	4,491	6,272	7,326	9,044	973	23,670
3545	1/16"	162.1	0.379	1.35E-09	927	2,217	3,361	4,079	5,303	18,209	61,985
3545	1/8"	92.48	0.468	2.50E-03	799	2,349	3,930	4,992	6,907	4,460	53,307
3545	3/16"	628	0.249	7.93E-05	1,977	3,507	4,611	5,236	6,222	373	
3561	1/16"	72.3	0.466	2.16E-01	618	1,808	3,016	3,827	5,286	1,688	21,755
3591	1/16"	35	0.582	1.90E-04	517	1,975	3,745	5,041	7,547	1,410	29,194
3594	1/16"	151	0.41	1.64E-05	998	2,564	4,023	4,961	6,591	10,318	41,724
3594	1/8"	66	0.523	4.98E-06	739	2,462	4,373	5,712	8,208	6,308	24,174
3700	1/8"	1,318	0.258	6.00E-01	4,324	7,833	10,400	11,865	14,188	373	
5500	1/16"	1,247	0.249	1.10E+01	3,925	6,964	9,155	10,397	12,356	373	
9850	1/16"	1,591	0.239	9.30E+00	4,784	8,296	10,787	12,182	14,385	141	110,005
9900	1/16"	2,322	0.133	1.80E+01	4,283	5,817	6,731	7,208	7,899	199	128,434
ST-706	1/16"	2,455	0.267	6.22E-01	8,396	15,526	20,818	23,860	28,711		
Tex-O-Lon	1/8"	695	0.189	54	1,660	2,564	3,156	3,476	3,963	67	36,505
GRAPHONIC	1/16"	315	0.36	1.857	1,653	3,787	5,624	7,515	8,676		110,685
3123	1/16"	970	0.384	0.05	5,686	13,765	20,989	25,537	33,325		
3125SS	1/16"	816	0.377	0.066	4,631	11,033	16,694	20,240	26,284		
3125TC	1/16"	1400	0.324	0.01	6,225	13,126	18,738	22,110	27,678		
3128	1/16"	787	0.4	0.00287							