


<h2>STYLE 5000</h2>		
<b>DESCRIPTION</b>	Premium carbon packing option able to handle several demanding conditions happening at the same time and when/where flush contamination is prohibited. Style 5000 is a tough, low-abrasion carbon fiber packing impregnated with PTFE and treated with a high temperature break-in lubricant.	
<b>APPLICATION</b>	<ul style="list-style-type: none"> <li>• High temperature Pump and Valve services.</li> <li>• High speed pumping applications.</li> <li>• Chemically aggressive media including strong acids, bases, and solvents</li> <li>• Abrasive media</li> </ul>	
<b>FEATURES/BENEFITS</b>	<ul style="list-style-type: none"> <li>• Most versatile non-contaminating packing available to limit application specific stocking needs.</li> <li>• Contains no graphite for limited color contamination</li> <li>• High abrasion resistance for increased packing life</li> <li>• Class leading conformability and easy fitting for quicker installation and start-up</li> </ul>	
<b>TEMPERATURE</b>	-328°F to +600°F	(-200°C to +315°C)
<b>SHAFT SPEED</b>	To 3000 FPM	To 15 m/sec
<b>PRESSURE</b>	To 500 psi in rotary pump service	To 35 Bar in rotary pump service
<b>PH RANGE</b>	0 - 14 (Except strong oxidizers)	
<b>CONSTRUCTION</b>	LATTICE BRAID carbon fiber packing with PTFE coating	